

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/109992 A1

(51) International Patent Classification⁷: H04L 12/56,
12/28, G06F 19/00, A61B 5/00

[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(21) International Application Number:
PCT/IB2004/050785

(72) Inventors; and

(75) Inventors/Applicants (for US only): KLABUNDE,
Karin [DE/DE]; c/o Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).
MUESCH, Guido [DE/DE]; c/o Philips Intellectual Prop-
erty & Standards GmbH, Weissshausstr. 2, 52066 Aachen
(DE).

(22) International Filing Date: 27 May 2004 (27.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03101659.5 6 June 2003 (06.06.2003) EP

(74) Agent: VOLMER, Georg; Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).


(71) Applicant (for DE only): PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

(71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N. V.

[Continued on next page]

(54) Title: METHOD OF CONTROLLING WIRELESS DATA TRANSMISSION BY SWITCHING BETWEEN SHORT-RANGE
AND LONG-RANGE RADIO TECHNOLOGIES



(57) Abstract: The invention relates to a device, in particular a patient monitoring system with a mobile terminal unit (1) for acquiring patient data. The measured data is transferred from the terminal unit (1) via a short-range radio technology (2) (e.g. Bluetooth) to a data monitor (3) arranged at the patient's bedside when the patient is in the vicinity thereof. If necessary, communication can be switched to a long-range radio technology (7) (e.g. WLAN) to ensure interruption-free data transmission while the patient moves around.